



LIGHTING EQUIPMENT LIST

Ver. 2025.04.21

Local Power Supply

230 volt single phase, 60Hz					
Standard stage fixture connector		20A Stage Pin Connectors			
Standard household connector		20A PP2PGCM & Pro Series PS19 (19 Pin Connectors)			

Control System

Console	grandMA3 Light	2	Mode 3 = 16,384 Parameters Mode 2 = 4,096 Parameters	MA Lighting	
Processing	grandMA3 Processing Unit L	1	Mode 3 = 8,192 Parameters Mode 2 = 4,096 Parameters		
Backup System	grandMA3 Light With Switcher (Backup 4 Switch RS 8000N)				

Dimming System

Sensor+	Dimmer Module	139	5kW	ETC	278 Circuits (Dual)
	Direct Module	20			40 Circuits (Dual)
	ThruPower Module	5			10 Circuits (Dual)

Fixture

Source-Four Zoom	15° - 30°	36	750W	ETC	EDLT
	25° - 50°	36			
Source-Four Standard	19°	12			
	26°	48			
	36°	48			
	50°	12			
Lens Tube	5°	2		Marumo	With Barn door
	10°	2			
Fresnel	FQH-1000W S1	30	1kW	Kupo	VNSP, NSP, MFL, WFL
	FQH-2000W S1	6	2KW		
Par Light	Par64	60	1kW	Altman	1 Set = 8EA / ACL
	Par46	20 Sets	250W		
Zip Strip	ZS-3	4 Sets	1.5kW Per Circuit	Ushio	1 Set = 3 Circuit / ACL
Follow Spot Light	SUPERSOL 2009SR/e	2	2kW		Fixed

Effect

Strobe	Atomic 3000 DMX	2	3kW	Martin	
--------	-----------------	---	-----	--------	--

Accessory

Iris		25		Kupo	For Source-Four
Top Hat	Half	12	4 Inch		For Source-Four Standard
	Wide	12	4 Inch		
	Standard	72	4 Inch		
		60	6 Inch		For Source-Four Zoom
T - Pipe		30	60cm (W)		
Stand	Long	10	2.5 m		
	Middle	10	1 m		
	Short (SHB-5)	10	6 cm (H)	Marumo	
Side Arm		16	90 cm (H)	Altman	
		10	60 cm (H)		
Ladder		4	145 cm (H) x 120 cm (W)		
		4	80 cm (H) x 120 cm (W)		