

■ Space111 LIGHTING EQUIPMENT

Local Power Supply

230 volt single phase, 60Hz

Standard stage fixture connector ProPin Professional Stage Pin Connectors

Standard household connector 20A PP2PGCM

Additional Power

3-phase 4-wire system 50 ampere distribution, on Stage Left

1

3-phase 4-wire system 75 ampere distribution, on Stage Right

1

Control Console

Console

E.T.C

ION

2

Accessory

E.T.C

Net3 Gateway 4 Ports

1

Backup System : ION Console With Switcher(Backup 4 Switch RS 4000N)

Dimming System

Dimmer	E.T.C	Sensor3	1 Set	5kW / 84 Dimmer (Dual Type)
				5kW / 12 ThruPower (Dual Type)
		Sensor+	1 Set	5kW / 40 Dimmer (Dual Type)
				5kW / 8 ThruPower (Dual Type)
			1 Set	5kW / 12 Dimmer (Dual Type)
			1 Set	5kW / 24 Dimmer (Dual Type)

E.R.S	26°	E.T.C	Source-Four Standard / 750W	12	EDLT
	36°			24	
	50°			24	
	70°			6	
	90°			6	
	Zoom 25° ~ 50°		Source-Four Zoom	24	
Spare Tube	70°	Marumo		12	
	90°			12	
Fresnel			FQH - 650W S1	36	With Barn door
			FQH - 1000W S1	18	
			MSM 805 - 1000W S1	12	

Light

PAR64 CAN	Order Made	1kW	50	
PAR46 CAN		250W	10 sets	1 Set = 8ea / ACL
Flood	Selecon	Lui / 1kW	10	With Barn door
Zip Strip	Altman	Z3 / 75W	4 sets	1 Set = 2ea / ACL

Effect

Hazer Fog	Look Solutions	UNIQUE 2	3	With Hanging Bracket
Fog	Look Solutions	Viper 2.6	1	
Fog Fan	Martin	JEM AF-1	2	
Film Machine	Gam	Film/FX	4	
Gobo Rotator	Apollo	Smart Move	12	With Power Supplies 4ea
Strobe	Martin	Atomic 3000 DMX	1	

Stand

Long	Order Made	2.5m	10	
Middle		1m	10	
Short		0.3m	10	
T - Pipe		0.6m	30	
Ladder		145cm(H) x 120cm(W)	4	
Ladder		80cm(H) x 120cm(W)	4	

Accessory

Top Hat	Order Made	4 Inch	36	For S/4 Standard
		6 Inch	16	For S/4 Zoom
		8 Inch	12	For PAR 64
	Half	4 Inch	12	For S/4 Standard
	Wide	6 Inch	12	For S/4 Zoom
Source-Four Iris	E.T.C		15	