

## ■ Space111 LIGHT EQUIPMENT

### Local Power Supply

230 volt single phase, 60Hz

Standard stage fixture connector ProPin Professional Stage Pin Connectors

Standard household connector 20A PP2PGCM

### Additional Power

3-phase 4-wire system 50 ampere distribution, on Stage Left

1

3-phase 4-wire system 75 ampere distribution, on Stage Right

1

### Control Console

Console

E.T.C

ION

2

Accessory: Net3 Gateway 4 Ports

Universal Fader Wing (2 \* 20) 2ea, 21.5" Touch Monitor 2ea

Back up System : Use Ion Console Connected to Console For Back up System

### Dimming System

Dimmer	Lee Colotran	i96Dimmer	1 Set	5.4kw / 96 Dimmer (Dual Type)
Direct Module			5	5kw / (Dual Type)
Dimmer	E.T.C	Sensor3	1 Set	5kw / 40 Dimmer (Dual Type)
				5kw / 8 ThruPower(Dual Type)
		Sensor+	1 Set	5kw / 12 Dimmer (Dual Type)
			1 Set	5kw / 24 Dimmer (Dual Type)

E.R.S 26°	E.T.C	Source-Four Standard / 750w	12	EDLT
36°			24	
50°			24	
70°			6	
90°			6	
Zoom 25° ~ 50°		Source-Four Zoom	24	
Spare Tube 70°			12	
90°			12	
Fresnel	Marumo	FQH - 650w S1	36	With Barn door
		FQH - 1000w S1	18	

### Light

PAR64 CAN	Order Made	1kw	40	
PAR46 CAN		250w	10 sets	1 Set = 8ea / ACL
Flood	Selecon	Lui / 1kw	10	With Barn door
Zip Strip	Altman	Z3 / 75w	2 sets	1 Set = 2ea / ACL

### Effect

Hazer Fog	Look Solutions	UNIQUE 2	3	With Hanging Bracket
Fog	Look Solutions	Viper 2.6	1	
Fog Fan	Martin	JEM AF-1	2	
Film Machine	Gam	Film/FX	4	
Gobo Rotator	Apollo	Smart Move	12	With Power Supplies 4ea
Strobe	Martin	Atomic 3000 DMX	1	

### Stand

Long	Order Made	2.5m	10	
Middle		1m	10	
Short		0.3m	10	
T - Pipe		0.6m	30	
Ladder		145cm(H) x 120cm(W)	4	
Ladder		80cm(H) x 120cm(W)	4	

### Accessory

Top Hat	Order Made	4 Inch	36	For S/4 Standard
		6 Inch	16	For S/4 Zoom
		8 Inch	12	For PAR 64
	Half	4 Inch	12	For S/4 Standard
	Wide	6 Inch	12	For S/4 Zoom
Source-Four Iris	E.T.C		15	