

■ YONGANG HALL LIGHT EQUIPMENT				
Local Power Supply				
230 volt single phase, 60Hz				
Standard stage fixture connector		ProPin Prdfessional Stage Pin Connectors		
Standard household connector		20A PP2PGCM & Pro Series PS19(19 Pin Connectors)		
Additional Power				
3-phase 4-wire system 150 ampere distribution, is situated Up-Stage Right.				
Main circuit breaker(MCCB) 150 ampere				
Sub circuit breaker(MCCB) 2ea 100, 50 ampere				
Control Console				
Console	MA Lighting	grand MA full-size	1ea	
Accessory: NSP 1ea				
Back up System : Use Laptop connected to Console for back up system				
Dimming System				
Dimmer	E.T.C	Sensor+	3sets	5kw/ 288 Dimmer (Dual Type)
Moving Light				
Moving Light	Vari	3500 Spot	4ea	
	Vari	3000 Spot	16ea	
Spot Light				
E.R.S	19°	Source-Four Standard / 750w	12ea	EDLT
	26°		48ea	
	36°		48ea	
	50°		12ea	
	Zoom 15° ~ 30°	Source-Four Zoom	36ea	
	Zoom 25° ~ 50°		36ea	
Spare Tube	5°		2ea	
	10°		2ea	
	70°		6ea	
	90°		6ea	
Fresnel	Marumo	FQH - 1000w S1	30ea	With Barn door
		FQH - 2000w S1	6ea	
Follow	Lycian	Stark Lite 2 / 1.2kw	4ea	Portable
	Ushio	Xevex - 2000w	2ea	Fixed
Light				
PAR64 CAN	Order Made	1kw	80ea	
PAR46 CAN	Order Made	250w	20sets	1 Set = 8ea / ACL
Flood	Selecon	Hui / 500w	6ea	With Barn door
		Lui / 1kw	6ea	
Zip Strip	Altman	Z3 / 75w	6sets	1 Set = 2ea / ACL
Effect				
Hazer Fog	Look Solutions	UNIQUE 2	2ea	With Hanging Bracket
Strobes	Martin	Atomic 3000 DMX	2ea	
Stand				
Long		2.5m	10ea	
Middle		1m	10ea	
Short		0.3m	10ea	
T - Pipe		0.6m	30ea	
Accessory				
Top Hat		4 Inch	72ea	For S-4 Standard
	Order Made	6 Inch	50ea	For S-4 Zoom
		8 Inch	24ea	For PAR 64
Source-Four Iris	E.T.C		25ea	

