

■ YONKANG HALL LIGHT EQUIPMENT

Local Power Supply

230 volt single phase, 60Hz

Standard stage fixture connector ProPin Professional Stage Pin Connectors

Standard household connector 20A PP2PGCM & Pro Series PS19(19 Pin Connectors)

Additional Power

3-phase 4-wire system 150 ampere distribution, is situated Up-Stage Right.

Main circuit breaker(MCCB) 150 ampere

Sub circuit breaker(MCCB) 2ea 100, 50 ampere

Control Console

Console	MA Lighting	grand MA full-size	1	
---------	-------------	--------------------	---	--

Accessory: NSP 1ea

Back up System : Use Laptop connected to Console for back up system

Dimming System

Dimmer	E.T.C	Sensor+	3 sets	5kW / 288 Dimmer (Dual Type)
Direct Module	E.T.C	Sensor+	20	5kW / (Dual Type)

Spot Light

E.R.S	19°	E.T.C	Source-Four Standard / 750W	12	EDLT
	26°			48	
	36°			48	
	50°			12	
Zoom	15° ~ 30°		Source-Four Zoom	36	
Zoom	25° ~ 50°			36	
Spare Tube	5°			2	
	10°			2	
Fresnel		Marumo	FQH - 1000W S1	30	With Barn door
			FQH - 2000W S1	6	
Follow		Lycian	Stark Lite 2 / 1.2kW	4	Portable
		Ushio	Xevex - 2000W	2	Fixed

Light

PAR64 CAN	Order Made	1kW	80	
PAR46 CAN	Order Made	250W	20 sets	1 Set = 8ea / ACL
Flood	Selecon	Hui / 500W	10	With Barn door
Zip Strip	Altman	12V / 75W	6 sets	1 Set = 2ea / ACL

Effect

Strobes	Martin	Atomic 3000 DMX	2	
---------	--------	-----------------	---	--

Stand

Long	Order Made	2.5m	10	
Middle		1m	10	
Short		0.3m	10	
T - Pipe		0.6m	30	
Ladder		145cm(H) x 120cm(W)	4	
Ladder		80cm(H) x 120cm(W)	4	

Accessory

Top Hat	Order Made	4 Inch	72	For S/4 Standard
		6 Inch	50	For S/4 Zoom
		8 Inch	24	For PAR 64
	Half	4 Inch	12	For S/4 Standard
	Wide	6 Inch	12	For S/4 Zoom
Source-Four Iris	E.T.C		25	